

# Quick Connect Fittings Series Datasheet

Website: 47.82.152.203

Email: louisxiecq@gmail.com

WhatsApp: +86 159 1919 9144

## Quick Connect Fittings Series

These push-in fittings help build clean pneumatic layouts with fast installation, stable sealing, and easy maintenance for tube-based air systems.

## Series Comparison

### Series

#### Structure

#### Main Function

#### Common Sizes

#### PC Series

Straight male connector

Connect tube to threaded port

4 to 16 mm

#### PL Series

Male elbow connector

Change direction at port

4 to 16 mm

#### PB Series

Male branch tee

Threaded branch distribution

4 to 12 mm

#### PE Series

Union tee

Tube-to-tube branch routing

4 to 12 mm

#### Supply Support

Model selection support for bore size, stroke, thread type, voltage, or mounting accessories.

OEM, wholesale, and export packaging support.

Fast quotation response for standard and customized demand.

Request A Quote

Contact Us

#### FAQ

How do I choose between PC, PL, PB, and PE fittings?

PC is straight, PL is elbow, PB is branch tee with thread, and PE is union tee for tube-to-tube connection. The right choice depends on routing direction and port structure.

What tube sizes are commonly supported?

Common tube outer diameters include 4 mm, 6 mm, 8 mm, 10 mm, and 12 mm. Larger sizes may also be available depending on the fitting series.

# Quick Connect Fittings Series Datasheet

Can I use these fittings for vacuum as well as air?

Many pneumatic push-in fittings can be used for vacuum and compressed air applications within the rated pressure range.

[PDF Download](#)

[Download Quick Connect Fittings Series PDF Datasheet](#)

This downloadable sheet includes the main specifications, model references, and application notes shown on this page.